

FIBRE GLASS MESH ULTRAFLEX

Glass fibre mesh that reinforces the microcement.



Always on floors, and on walls with tiles, joints or unevenness. Roll out tight without folds, Primer PLUS on top.

CONSUMPTION	1 m ² per running metre of the roll
-------------	--

PACKS	10 m ² , 50 m ²
-------	---------------------------------------



UPDATE FROM CIMENTART HQ, 28/10/2026

- On tiles, joints and uneven surfaces always with mesh and base. On smooth walls (wood, MDF, filler, painted plasterboard) the mesh is not needed.

Where this differs from the data sheet below, this applies.

OVERVIEW

- Increased resistance to structural movements
- Easy to install
- Prevents surface cracking
- 100% natural fibers
- Makes easier the application of any cement product

The FIBRE GLASS MESH CIMENTART is recommended to increase the resistance in Microcement floors, when facing the tensions that are created at certain points of a building our house.

It is a security element, and adds quality to the installation by reducing the risk of cracking produced by a concentration of tensions or possible movements in the building.

The FIBRE GLASS MESH CIMENTART is anti-slip, which helps to the application of the BASE MICROCEMENT and by itself is very flexible and resistant.

TECHNICAL DATA

Fiber Mesh size	1 x 3 mm
Color	White
Weight	60 gr / m2, 2,11 Oz / 10 sq ft
Tensile Strength	484 kg / Inch
Thread	Natural fibers 100 % polyester glass
Treatment	at 100 °C without deformation
Melting Point	840 °C - 1544 F
Efficiency	50 m2 - 538,21 sq ft
Shipping	Material not dangerous
Storing	Material not dangerous

HOW TO USE

Extend the FIBRE GLASS MESH CIMENTART at the surface you are going to work with, by covering completely.

Once extended, use CIMENTART Primer PLUS to make stick and do not move during the installation process.

E F F I C I E N C Y

With the width of the roller you can cover 1 m² / 10,66 sq ft for each linear meter.

P R E S E N T A T I O N

Rollers with 50 m² / 538,21 sq ft.

S T O R I N G

Do not expire. Store in a dry place protected from bad weather.

O V E R V I E W

CIMENTART MICROCEMENT SL. Our systems are based in the research done at our laboratories and the many years of practical experience we have. We guarantee that our products are manufactured, packaged and labeled under the rules of Normative ISO 9001:2008. We decline any responsibility if the end result is affected by external factors not under our control. The end user must check that the product supplied is adequate to the needs that is going to be used for, doing a test in any case that must be necessary.

Review date: 30-08-18.

The present document cancels the earlier editions.

The full text of the official CimentArt technical data sheet.